

Fitting piece

Plastic

Fitting piece is suitable for installation as a placeholder for a water meter when first installing a drinking water distribution network or for flushing a drinking water system.

Performance characteristics

- for cold- and warm water meter (max. 85 °C)
- made of composite glass-fiber-reinforced plastic
- German drinking water approval according to KTW/W270



Attention

Plastic fittings must not be used for more than 2 years under pressure. For long-term use or beyond 2 years, brass or steel fittings should be used.

Technical data						
Meter size	Q ₃	1.6-2.5 m ³ /h	1.6-2.5 m ³ /h	1.6-2.5 m ³ /h	4 m ³ /h	4 m ³ /h
Meter size	Q _n	1.0-1.5 m ³ /h	1.0-1.5 m ³ /h	1.0-1.5 m ³ /h	2.5 m ³ /h	2.5 m ³ /h
Pressure load max.	bar	10	10	10	10	10
Nominal diameter	DN	15	15	15	20	20
Connecting sizes	Inch	½	½	½	¾	¾
Thread size	Inch	G ¾"	G ¾"	G ¾"	G 1"	G 1"
Total length	mm	80	110	170	130	190
Wrench size	mm	24	24	24	32	32
Material		PPE	PPE	PPE	PPE	PPE
Temperature load max.	°C	85	85	85	85	85
Order number						
		100528	100070	155367	114608	141250

ZENNER International GmbH & Co. KG

Römerstadt 6 | 66121 Saarbrücken | Germany

Phone +49 681 99 676-30

E-Mail info@zenner.com

Telefax +49 681 99 676-3100

Internet www.zenner.com

ZENNER